## GROUP 600 ACCESORIES MOD. 633/126



# TECHNICAL Data Sheet

# **WATER Series**

WIDE RANGE DUCTILE IRON REPAIR CLAMP PN10/PN16

www.davincivalves.com

DAVINCI

VALVES

PRODUCT OT

DAVINCI VALVES

COMPANY QT ASSUREMENT

DAVINCI

**VALVES**<sup>™</sup>

QUALITY ASSUREMENT



10F/Tower A, Billion Center, 1 Wang Kwong Road, Kowloon Bay Kowloon HONG KONG



#### WIDE RANGE DUCTILE IRON REPAIR CLAMP PN10/PN16 Ref.633A

#### **APPLICATION:**

Water, HVAC installations, irrigation, industry, others

#### **WORKING CONDITIONS:**

Working Temperature: - 10 °C - + 120 °C. for EPDM - 10 °C - + 82 °C. for NBR

#### **GENERAL CHARACTERISTICS:**

Size DN80 to DN300, working pressure PN10/PN16 Body pn16

#### **STANDARDS:**

Comply with EN545

#### **Material specification**

No.	Parts Name	Materia	
1	Body	Ductile iron	
2	Gasket	EPDM	
3	Bolts	Gal.carbon steel	
4	Nuts	Gal.carbon steel	

#### Dimensions

DN	D	L	В
80	88-99	225	219
100	107-119	225	246
150	157-171	225	291
200	219-226	310	352
250	270-276	310	420
300	320-328	310	471


Surface can be Fusion Bonded Epoxy coating,nylon 11 coating or upon client request

All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice. © 2018 DAVINCI VALVES LTD.

www.davincivalves.com info@davincivalves.com +34 616553797 / +86 17340168233 18 Dongyu Street, Square One 11th Floor 1101. Jinjiang District, Chengdu, Sichuan Province, China





# **TECHNICAL DATA**

### "For profesionals who wants more"



www.davincivalves.com