


**GROUP 600  
FITTINGS &  
FLANGES  
MOD.  
640A/129**



**DAVINCI  
VALVES™**

**FICHA  
TECNICA**  
**WATER series**

**STUDED REDUCER FLANGE PN10/ PN16**

**DAVINCI  
VALVES™**



**QUALITY  
ASSUREMENT**

**DAVINCI  
VALVES™**



**PRODUCT QT  
ASSUREMENT**

**DAVINCI  
VALVES™**



**COMPANY QT  
ASSUREMENT**

[www.davincivalves.com](http://www.davincivalves.com)

18 Dongyu Street, Square One,  
11th Floor 1101, Jinjiang District,  
Chengdu, Sichuan CHINA

10F/Tower A, Billion Center,  
1 Wang Kwong Road, Kowloon Bay  
Kowloon HONG KONG

## STUDDED REDUCER FLANGE PN10/ PN16 Ref.640A

### WORKING CONDITIONS:

Working Temperature:  
- 10 °C - + 120 °C. for EPDM  
- 10 °C - + 82 °C. for NBR

### GENERAL CHARACTERISTICS:

Size DN40 to DN300,  
working pressure PN10/16  
Body pn16

### Material specification

No.	Parts Name	Material
1	Body	Ductile iron
2	Bolt and nut	Gal. carbon steel

**Flange standard:**EN1092-2

**Coating standard:**EN30677

**Test standard:** EN12266-1

### STANDARDS:

Comply with EN545



Surface can be Fusion Bonded Epoxy coating,nylon  
11 coating or upon client request

### Dimensions

DN	dn	L	Screwed	Weight(kg)
60	40	55	D M16(X8)	5.8
80	40	32	D M16(X8)	4.9
80	40	32	D M16(X12)	5.7
80	50	32	D M16(X8)	5.1
80	50	32	D M16(X12)	5.7
80	60	50	D M16(X8)	7.8
80	60	32	D M16(X12)	5.7
80	65	32	D M16(X12)	5.7
100	40	32	D M16(X12)	6.1
100	60	32	D M16(X12)	6
100	65	32	D M16(X12)	6.1
100	80	55	D M16(X12)	9.6
100	80	55	D M16(X12)	9.9
125	60	32	D M16(X12)	7.7
125	65	32	D M16(X12)	7.7
125	80	32	D M16(X12)	8.2
125	80	32	D M16(X16)	8
125	100	55	D M16(X16)	12.4
150	60	37	S M16(X4)	10.2
150	65	37	S M16(X4)	10.2
150	80	32	S M16(X4)	8.1
150	80	32	S M16(X8)	8.7
150	100	32	D M16(X8) M20	10.2
150	125	55	D M16(X8) M20	15.3
200 PN10/16	60	55	S M16(X4)	20.5
200 PN10/16	65	55	S M16(X4)	20.5
200 PN10/16	80	50	S M16(X4)	13.8
200 PN10/16	80	50	S M16(X8)	19
200 PN10/16	100	50	S M16(X8)	13.4
200 PN10/16	125	38	S M16(X8)	14.5
200 PN10	150	32	D M20(X16)	14.3
200 PN16	150	32	D M20(X20)	14.7
250 PN10	100	35	S M20(X8)	17
250 PN10	200	35	D M20(X20)	18.3
300 PN10	200	35	S M20(X8)	20
300PN10	250	35	D M20(X20)	21.8


Please note dimension may vary at our discretion

All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.  
© 2018 DAVINCI VALVES LTD.

www.davincivalves.com info@davincivalves.com +34 616553797 / +86 17340168233  
18 Dongyu Street, Square One 11th Floor 1101. Jinjiang District, Chengdu, Sichuan Province, China

*"For professionals who wants more"*



DAVINCI  
VALVES™