


**GROUP 200
COMPLEMENTS
MOD. 240/86**



**DAVINCI
VALVES™**

**TECHNICAL
DATA SHEET**

FIRE Series

**HYDRANT
SYSTEM UL/FM**

**DAVINCI
VALVES™**



**QUALITY
ASSUREMENT**

**DAVINCI
VALVES™**



**PRODUCT QT
ASSUREMENT**

**DAVINCI
VALVES™**



**COMPANY QT
ASSUREMENT**

www.davincivalves.com

18 Dongyu Street, Square One,
11th Floor 1101, Jinjiang District,
Chengdu, Sichuan CHINA

10F/Tower A, Billion Center,
1 Wang Kwong Road, Kowloon Bay
Kowloon HONG KONG

DRY BARREL HYDRANT POST UL/FM FIRE SYSTEMS

Ref. 240A

STANDARDS:

Design Standard AWWA C502

WORKING CONDITIONS:

Nominal Pressure: 250PSI

Working Temperature: -10C +100C

Suitable Media: Water

GENERAL CHARACTERISTICS:

One pumper nozzle 4.5-4NH thread. Two hose nozzles 2.5-

7.5NH threads. Other kinds of threads are available

Mechanical connector AWWA/ANSI C153/A21.53 6"

Flange connector ASME B16.5 CLASS150/DIN2501 PN16

SIZE	L
3"-6"	1063
4"	1215
5"	1368
4'6' "	1520
5'6"	1673
6"	1825
6'6"	1978
7"	2130



All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.
© 2018 DAVINCI VALVES LTD.

DRY BARREL HYDRANT POST UL/FM FIRE SYSTEMS


Ref. 240A

NO.	ITEM	Qty.	Material	Remark
1	FLANGE CONNECTOR/ MECHANICAL CONNECTOR	1	DI	
2	LOCKING NUT	1	DI	
3	CONNECTING ROD	1	1045	ASTM A29/29M
4	LOCKING NUT GASKET	1	EPDM	
5	TRAY	1	DI	
6	SEALED RUBBER SHEET	1	EPDM	
7	GULD BRACKET	1	C95400	ASTM B148
8	CONNECTING CYLINDER	1	DI	
9	PERFORATED CYLINDRICAL PIN	2	1045	ASTM A29/29M
10	CONNECTING ROD SLEEVE	1	1045	ASTM A29/29M
11	CLAMP FOR CONNECTION TUBE	1	DI	
12	MAIN BODY ON GROUND	1	DI	
13	CONNECTOR DN65	2	C95400	ASTM B148
14	COVER GASKET DN65	2	EPDM	
15	COUPLING DN65	2	DI	
16	UPPER END COVER	1	DI	
17	THREAD PLUG	1	C95400	ASTM B148
18	SCREW STEM NUT	1	C95400	ASTM B148
19	SCREW NUT GASKET	1	C95400	ASTM B148
20	SCREW NUT SEAT	1	C95400	ASTM B148
21	BOLTS & NUTS	8	1035	ASTM A29/29M
22	COUPLING DN100	1	DI	
23	CYLINDRICAL PIN	1	1045	ASTM A29/29M
24	COVER CHAIN	3	GR. B	ASTM A283-B
25	BOLTS& NUTS	8	1035	ASTM A29/29M
26	SCREW STEM	1	1045	ASTM A29/29M
27	CUSHION RUBBER	1	EPDM	
28	PRESSURE RELIEF VALVE		SS304	ASTM A240
29	SEAT		C95400	ASTM B148
31	SEAT FIXING PLATE	1	DI	
32	BOLTS & NUTS	1	1035	ASTM A29/29M
33	ANNUAR TUBES	8	1045	ASTM A29/29M
34	PLATEN	1	DI	
35	LOCKING NUT SEAT	1	DI	
36	CHECK TURN GASKET	1	GR. B	ASTM A283-B
37	CONNECTOR DN100	1	C95400	ASTM B148
38	COVER GASKET DN100	1	EPDM	FIGURE NOT SHOWN
39	SCREW STEM BUSHING	1	304	ASTM A240
40	BOLT	2	304	ASTM A240

All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.
© 2018 DAVINCI VALVES LTD.

"For professionals who wants more"



DAVINCI
VALVES™