GROUP 500 AUTOMATIC CONTROL VALVES MOD. 500A/100





TECHNICAL DATA SHEET

WATER Series

AIR RELIEF VALVES THREADS END







www.davincivalves.com

WATER series



AIR RELIEF VALVE THREAD END PN10/16

ref.500A / THREAD END / PN 10-16-ANSI150#

APPLICATION:

Potable water distribution and pumping, irrigation

WORKING CONDITIONS:

Pressure Ratings: 1.0Mpa; 1.6Mpa Working Temperature: -10C +100C

Suitable Media: Water

End connection: PN 10/ PN 16 Consult Factory for other applications

GENERAL CHARACTERISTICS:


Range 1", With Flange ND40/50/60/65 & ND080/100 Epoxy paint cured 250 microns

STANDARDS:

Hydrostatic test according to EN 12266-1, class A.


EC directive

THread end GAS / NPT





Νo	ITEM	MATERIAL
1	BASE FLANGE	GGG40
2	BALL VALVE	BRASS NICKEL PLATED
3	BODY	GGG40
4	FLOATING BALL	ABS
5	SHAFT	BRASS
	AIR VENT PART	
6	Α	BRASS
7	GASKET	EPDM
8	GASKET	EPDM
9	BODY COVER	GGG40
	AIR VENT PART	
10	Α	BRASS



All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice. © 2018 DAVINCI VALVES LTD.

www.davincivalves.com info@davincivalves.com +34 616553797 / +86 17340168233 18 Dongyu Street, Square One 11th Floor 1101. Jinjiang District, Chengdu, Sichuan Province, China

"For profesionals who wants more"

