


**GROUP 600
ACCESSORIES
MOD.
635A/128**



**DAVINCI
VALVES™**

**TECHNICAL
DATA SHEET
WATER Series**

**ADJUSTABLE BELL JOINT REPAIR CLAMP
PN10**

**DAVINCI
VALVES™**



**QUALITY
ASSUREMENT**

**DAVINCI
VALVES™**



**PRODUCT QT
ASSUREMENT**

**DAVINCI
VALVES™**



**COMPANY QT
ASSUREMENT**

www.davincivalves.com

18 Dongyu Street, Square One,
11th Floor 1101, Jinjiang District,
Chengdu, Sichuan CHINA

10F/Tower A, Billion Center,
1 Wang Kwong Road, Kowloon Bay
Kowloon HONG KONG

ADJUSTABLE BELL JOINT REPAIR CLAMP PN16

Ref.635A

APPLICATION:

Water, HVAC installations, irrigation, industry, others

WORKING CONDITIONS:

Working Temperature:

- 10 °C - + 120 °C. for EPDM

- 10 °C - + 82 °C. for NBR

GENERAL CHARACTERISTICS:

Size DN50 to DN600,

working pressure PN10

Body pn16

STANDARDS:

Comply with EN545

Flange standard: EN1092-2



Material specification

No.	Parts Name	Material
1	Nut	Gal.carbon steel
2	Bolts	Gal.carbon steel
3	Spigot ring	Ductile iron
4	Gasket	EPDM
5	Bell ring	Ductile iron

Surface can be Fusion Bonded Epoxy coating,nylon

11 coating or upon client request

Dimensions

DN	Range Dmin-max(mm)
50	62-68
65	75-84
80	94-100
100	114-120
150	166-173
200	217-224
250	270-276
300	321-328
350	373-380
400	424-431
500	527-534
600	630-638

Please note dimension may vary at our discretion

All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.

© 2018 DAVINCI VALVES LTD.

www.davincivalves.com info@davincivalves.com +34 616553797 / +86 17340168233
18 Dongyu Street, Square One 11th Floor 1101. Jinjiang District, Chengdu, Sichuan Province, China

"For professionals who wants more"



DAVINCI
VALVES™